

- Maximum dry adhesion
- Prevents seam spreading and curling
- Strong wet tack

**Dynamite<sup>®</sup> 111 Heavy Duty Clay Non-Strippable Wallcovering Adhesive** contains high solids to assure fast grab and a strong, durable bond. This adhesive is ideally suited for all heavy and difficult-to-install wallcoverings such as Commercial Type III vinyl, heavyweight fabric, flexible wood, Mylar<sup>®</sup> and foil. Cleans up with water while wet.

**SURFACE PREPARATION:** Surface must be clean and free of oil, dust, dirt, grease, mildew, and other foreign matter. For best results, use **Dynamite All-Purpose Cleaner** to prepare walls. A diluted household bleach solution also works well to clean walls. Repair or fill cracks in the wall surface with **Dynamite Non-Shrink Spackling** prior to priming.

**Plaster** – New plaster must age at least 30 days before hanging wallcovering. Prime with **Dynamite 221** or **222**.

**Drywall** – New drywall must be wiped down with a damp cloth to remove dirt, grease, wax and peeling paint. Prime with **Dynamite 221** or **222**.

**Other Porous Surfaces** – Walls must be clean, dry, smooth and structurally sound. Prime with **Dynamite 221** or **222**.

**Glossy Surfaces** – Ceramic tile, glossy paint, existing vinyl wallcoverings, Formica<sup>®</sup>, glass, plastic or baked enamel should be primed with **Dynamite 221, 222** or **235**.

**Commercial Grade II & III** – Prime with **Dynamite 235** when hanging heavy weight commercial-grade papers.

**DO NOT USE OVER OIL/ALKYD PAINT/PRIMER OR VARNISH UNLESS IT IS PRIMED WITH A DYNAMITE ACRYLIC PRIMER.**

**APPLICATION:** Mix well before using to ensure even consistency. For lightweight wallcoverings, thin as needed, up to 1/4 pint of water per quart. Apply evenly, making sure sufficient adhesive is on edges and corners. Apply to wallcovering with a roller or stiff brush. Allow proper booking time according to the wallcovering manufacturer's hanging instructions. IMMEDIATELY remove adhesive from face of washable wallcoverings and adjacent surfaces with a clean, wet sponge. HANG WALLCOVERING ACCORDING TO THE MANUFACTURER'S HANGING INSTRUCTIONS.

**CLEAN-UP:** Immediately remove adhesive from the face of washable wallcoverings and adjacent surfaces with a clean, wet sponge. Dry with a clean, lint-free towel to check for paste residue. Clean equipment with water.

**COVERAGE:** Five gallons of adhesive will hang up to 40 single rolls. (1,400 sq. ft./5 gal.). Coverage rates can vary depending on condition of the substrate, priming and sizing, weather conditions and method of application.

**PRECAUTIONS:** For the longest life, store in controlled environment, 40 °F-80 °F. Do not store in direct sunlight. Do not store/warehouse product below 35 °F. Protect from freezing. Seal container when not in use. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not use in drinking water or food systems.

**QUALITY PROMISE:** Gardner-Gibson, Inc. promises that this product, when applied in accordance with our written directions in applications recommended by us as suitable for this product, will be free of defects in material. In the unlikely event that a defect should develop, and you notify us of such a defect within 12 months of purchasing product, and provide adequate proof of purchase, we will replace the defective product at no cost to you. This promise of quality is the sole and exclusive remedy for any such defective product. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE AND GARDNER-GIBSON, INC. WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

| AVAILABLE SIZES |           |                          |                 |             |        |              |
|-----------------|-----------|--------------------------|-----------------|-------------|--------|--------------|
| PRODUCT CODE    | UNIT SIZE | UNIT DIMENSIONS          | FILL LEVEL      | UNIT WEIGHT | PACK   | UPC          |
| 7111-3-20       | 1 gal.    | 7.625" x 7.625" x 7.825" | 1 gal. / 3.8 L  | 11 lbs.     | 4/case | 027134711121 |
| 7111-3-30       | 5 gal.    | 12.5" x 12" 14.75"       | 5 gal. / 18.9 L | 55 lbs.     | 1 ea.  | 027134711138 |